

BATEMAN



RB26



SPECIFICATIONS RB26

Dimensions (dependent upon specification)

Height	3.2m	Wheel Base	3.3m
Width	2.8m	Turning Radius	4.8m
Length	7.0m	Weight	6610kg
Ground Clearance	0.85m	Fuel Capacity	220 litres

Steering

Positive Link 2/4-wheel steer, fully hydraulic.

Suspension

Hydraulic fully active front and rear

Wheel Track

Hydraulic adjustable axles with variable track width

Engine and Transmission

John Deere 185hp 6-cylinder water cooled Turbo-charged diesel
Fully Hydrostatic four wheel drive, variable from 0 up to 40kph
Hydrostatic primary braking with manual park brake, automatically applied when the engine is stopped

Cab

Steel construction, with all round panoramic tinted glass
Rubber mounted suspension
Cladded and soundproofed
Carbon filtration
Automatic climate control system (heating and cooling)
Bluetooth CD/Radio player
Roof mounted 360 degrees working lights, and warning beacon
Wash wipe windscreen wiper – 3 speeds including intermittent wipe
Large extendable wing mirrors
Fresh water hand/eyewash
Pneumatically operated step
Air suspension seat with fore and aft movement
Raise, lower and tilting steering column
External airline pickup point

Sprayer

Tank, Stainless Steel	3000 litres fully baffled, tank contents gauge with dry indicator with built in clean water rinse tank
Boom	Bateman 12/20/24 metre Bateman Contour, Bateman 12/18/20/24 metre Bateman Contractor Contour; Both having 'Gull Wing' folding or Bateman (V.G.) Variable Geometry up to 36m V.G. boom options 12/20/24m 12/24/ to either 28-30-32-or 36m
Filling	4 cylinder 270 litre/min piston diaphragm pump Stainless steel chemical hopper, can wash/bowl rinse, with twin venturis Self-fill or bowser quick fill
Controls	LH5000 (GPS enabled) Electric tapping system giving in-cab control of tank and sprayline rinse Auto priming system Pneumatic diaphragm line valves Ramsay box
Demounting	Full set of demount legs and jacks

Wheels

Row crops 12.4/R38 (320/85R38) or 14.9/R34 (380/85R34)

Controls

Joystick Command arm forward / reverse and sprayline controls
Electro-hydraulic spray pump and boom controls

Example Options

Triplet nozzles with 3 sets of jets
Twin stainless steel spraylines including 2 sets of jets
Spreader skid unit, mudguards and demount jacks
Automatic Section Control
Low ground pressure tyres
Boom height control
400 litre/minute 6 cylinder spray pump
Twin spray pumps

Please contact us for your tailor made specification

We reserve the right to alter specifications without prior notice

Our policy is one of continuous development

BATEMAN

Bateman Engineering Ltd

Bycott, Chulmleigh, North Devon EX18 7DS

Tel: 01769 580439 Fax: 01769 581023

info@batemansprayers.com

www.batemansprayers.com

