

BATEMAN



RB35

SPECIFICATIONS RB35

Dimensions (dependent upon specification)

Height	3.3m	Wheel Base	3.3m
Width	2.8m	Turning Radius	4.8m
Length	7.0m	Weight	6970kg
Ground Clearance	0.96m (standard)	Fuel Capacity	220 litres

Steering

Positive Link 2/4-wheel steer, fully hydraulic

Suspension

Hydraulic fully active front and rear

Wheel Track

Hydraulic adjustable axles with variable track width

Engine and Transmission

John Deere 225hp 6-cylinder water cooled Turbo-charged diesel
Fully Hydrostatic four wheel drive, variable from 0 up to 45kph
Hydrostatic and Dynamic braking. Parking brake manually operated or automatically applied when the engine is stopped.

Cab

Steel construction, with all round panoramic tinted glass
Rubber mounted suspension
Cladded and soundproofed
Carbon filtration
Automatic climate control system
Bluetooth CD/Radio player
Roof mounted 360 degrees working lights, and warning beacon
Wash wipe windscreen wiper – 3 speeds including intermittent wipe
Large extendable wing mirrors
Fresh water hand/eyewash
Pneumatically operated step
Air suspension seat with fore and aft movement
Raise, lower and tilting steering column
External airline pickup point

Sprayer

Tank, Stainless Steel	4000 litres fully baffled, tank contents gauge with dry indicator
Boom	Bateman 12/20/24 metre Bateman Contour, Bateman 12/18/20/24 metre Bateman Contractor Contour, Both having 'Gull Wing' folding or Bateman (V.G.) Variable Geometry up to 36m V.G. boom options 12/20/24m 12/24/ to either 28-30-32-or 36m
Filling	4 cylinder 270 litre/min pump Stainless steel 30 litre chemical hopper, dual can wash and bowl rinse, with twin venturis Self-fill or bowser quick fill
Controls	LH5000 (GPS enabled) Electric tapping system giving in-cab control of tank and sprayline rinse Auto priming system Pneumatic diaphragm line valves Ramsay box
Demounting	Full set of demount legs and jacks

Wheels

Row crops 16.9/R34 (420/85R34) or 14.9/R34 (380/85R34)

Controls

Joystick Command arm forward / reverse and sprayline controls
Electro-hydraulic spray pump and boom controls

Example Options

Triplet nozzles with 3 sets of jets
Twin stainless steel spraylines with 2 sets of jets
Spreader skid unit, mudguards and demount jacks
Automatic Section Control
Low ground pressure tyres
Boom height control
400 litre/minute 6 cylinder spray pump, or twin pumps

Please contact us for your tailor made specification

We reserve the right to alter specifications without prior notice

Our policy is one of continuous development



BATEMAN

Bateman Engineering Ltd

Bycott, Chulmleigh, North Devon EX18 7DS

Tel: 01769 580439 Fax: 01769 581023

info@batemansprayers.com

www.batemansprayers.com

