

Comfort and flexibility

Ergonomics, Visibility and Optimization



ALPHA

evo VariTrack

Technical specifications

Tank	2500 l	3000 l
Pumps, type, l/min	463 – 276 / 463H – 322 l/min	
Booms	ALU, TWIN FORCE	
Controller	HC 9500	
Engine	6 cyl. Deutz TIER III 129 kW 175 hp / 190 hp on TWIN boom	
Transmission	Hydrostatic Easy Drive transmission 28 or 40 km/h	
Suspension	Mechanical with shock absorber	
Steering	Hydrostatic 4-wheel	
Track adjustment	Mechanical adjustable track / hydraulic as an option	
Turning radius (200 cm track width)	462 cm	
Weight (empty)*	7790 kg	7820 kg
Total length	(A)	821 cm
Total height (460/85R54)	(B)	385 cm
Width with Alu boom 24 – 32 m	(C)	255 cm
Width with TWIN (18 – 28 m)	(C)	300 cm
Track width (460/85R54)	(D)	180 – 265 cm
Wheel base	(E)	364 cm
Clearance (460/85R54)	(F)	102 cm
Rinse tank, l	330	
Clean water tank, l	15	
Filling capacity, l/min	800	
Filling capacity TurboFiller, l/min	125	

* Weight is with 28 TR4 aluminium boom

